

**ITC LIMITED – PSPD, UNIT: BOLLARAM****DEV SPECIFICATION SHEET**

Doc. No: SP/TES/FP/40	Ver. No: 7.0	Rev. No: 0.0	Page 1 of 1	Issue Date: 01.03.2024
Grade Name	FILOBEV PREMIUM 1S			
Grade Id	FBPR			
SPEC NO	1FBPR/CTX/PSPD/BOL/BEV			

SUBSTANCE (GSM)	CALIPER (µM)	BENDING RESISTANCE(L&W) mN		
Tappi T 410	Tappi T 411	Tappi T 556		
		MD	CD	GM
		72	31	47
		78	34	51
		88	38	58
		99	43	65
		112	49	74
		121	53	80
		128	56	85
		145	63	96
TOL : ± 5%	± 5%			±15%

PARAMETER	UNITS	VALUE
COBB (3 Mins)	GSM	35 MAX ZERO
TOP		
BACK		
QS/TM/09 , Tappi T441		
MOISTURE	%	6 ± 1
Tappi T 412		
ROUGHNESS - PPS	ml/min	2.8 MAX
(Avg.)		
TOP		
Tappi T555		
EDGEWICK - LA/23	Kg/m²/Hour	1.4 MAX
TP84010		
STRETCH	%	2.0 MIN 5.0 MIN
MD		
CD		
Tappi T 494		

Construction

- Note :**
- 1.) All Properties are according to ITC Limited, PSPD Unit:BOL Measurements
 - 2.) Test Climate 23°C ± 1 & 50% ± 2 RH
 - 3.) Tolerances are based upon 95% Confidence limits of single mill measurements of conditioned random samples
 - 4.) This product can be serviced with FSC Mix. Certificate Registration Code: SW CoC 004747 - B

ACCEPTED BY	HEAD MARKETING (PSPD)	ISSUED BY	UNIT HEAD (BOL)
SIGNATURE		SIGNATURE	